

Easee

Charge Max

A home electric car charger designed to deliver accurate energy readings, transparent billing and complete charging cost control through an integrated MID compliant energy meter. Future-proof with over-the-air software updates and V2G-ready hardware.

Powerful. Accurate. Durable.

Features

Charge Max can charge up to 7.4 kW on a single-phase circuit, and up to 22 kW on a three-phase circuit. Install up to three chargers at one home site. The charger is continuously updated with the latest functionality.

- A MID Class B accuracy, according to EN 50470-3.
- Easee LinkTM Local Load & Phase balancing.
- Automatic queuing system.
- Permanent locking of the Type 2 cable.
- Integrated RFID reader (NFC / ISO 14443 and MIFARE Classic®).
- Universal, fits all types of electric cars & power supplies.
- Full control with the Easee App or third-party integrations.
- Manufacturer warranty: 5 years in accordance with Easee's warranty procedure.

Safety

Protection
Integrated RCD type A 30 mA AC according to EN 60947-2.
Integrated RDC-DD 6mA DC complying with IEC 62955, 9.9.
Temperature monitoring.
Overload protection.
Degree of protection: IP54 (the backplate is IP22 without cover).
Impact resistance: IK10.
Overvoltage category III.
Theft protection.
Read more at easee.com/manuals

Complies with the following regulations
2014/53/EU (RED).
2011/65/EU (RoHS).
2014/30/EU (EMCD).
2014/35/EU (LVD).
MID 2014/32/EU.
The Electric Vehicles (Smart Charge Points) Regulations 2021.
See DoC for details at easee.support

Technical

Charging power
1-phase: 1.4 kW (6 A) - 7.4 kW (32 A).
3-phase TN: 4.1 kW (6 A) - 22 kW (32 A).
3-phase IT: 2.4 kW (6 A) - 12.7 kW (32 A).

Electrical
Voltage: 3x 230 V / 400 V AC (+/-10%).
Grid frequency: 50 Hz.
Power grid: TN, IT, TT.
Connection point: Type-2 socket (Mode 3).
Automatic adjustment of charging speed based on available current.
Automatic charging with solar generation.[1]
Automatic phase balancing.
Built-in energy meter MID Class B (±1 %).
Hardware prepared for bidirectional charging (V2G)

Connectivity
Wi-Fi 2.4 GHz b/g/n.
Bluetooth BLE 4.2.
Built-in LTE Cat M1.
OCPP 1.6J.
Easee LinkRF (Local communication between chargers and to the Equalizer).
Built-in RFID/NFC reader for access control.
Easee App & Easee Control for control and monitoring.
IEC 61851-1 & ISO 15118

General
Dimension (mm): H: 256 x W: 193 x D: 106.
Wall mounting (mm): c/c H: 160 x W: 125.
Operating temperature: -30 °C to +40 °C.
Weight: 1.6 kg.

Easee App

Reliable local control
Get powerful local control of your charger by connecting via Bluetooth and get access to many useful features.

- Control charging.
- View charger status.
- Lock/unlock charging cable.
- Authorize charging with app.
- Charging session summary.
- Lifetime consumption counter.
- Available energy overview.
- Configuration.

1. Easee Equalizer required.

The information in this document is for information purposes only, is provided as is, and may be subject to change without notice. Easee IP AS, including its subsidiaries, does not accept any liability for the correctness or completeness of the information and illustrations, and is not liable or responsible for your considerations, assessments, decisions or absence of such, or other use of the information in this document.

No part of this publication may be re-published, reproduced, transmitted or re-used in any other form, by any means or in any form, for your own or any third-party's use, unless otherwise agreed with Easee or its subsidiaries in writing. Any permitted use shall always be done in accordance with good practice and ensure that no harm may be caused to Easee or by misleading the consumer.

Easee and Easee products, product names, trademarks and slogans, whether registered or not, are Easee's intellectual property and may not be used without Easee's prior written permission. All other products and services mentioned may be trademarks or service marks of their respective owners.

The latest version of this publication can be downloaded at **http://easee.support**

November 2026 - Version 1.03
© 2026 by Easee IP AS. All rights reserved.

Easee IP AS
Vassbotnen 23
4033 Stavanger, Norway
Org.nr: 920 292 046

Easee is distributed and maintained by a network of qualified partners and resellers. Find more information and your local partner at:

www.easee.com